

KAWASAKI MEAN STREAK TEARDROP LICENSE COVER

LowandMean.com 928.680.6660

Part # LM-01-301

INSTRUCTIONS

LM-01-301 includes:		WARNING: Do not install with the engine warm. This is an install at your own risk. If you feel you are not capable of installing this successfully then we highly suggest you
1	Rubber washer	take this item to a professional shop. Always check the fit before sending this product off to paint.

Suggestions for install:

Bending your license plate:

- You must bend your license plate to fit inside of the teardrop license cover (TLC).
- Start by bending up the bottom edges below the license plate numbers. (See image A & C)
- Next, bend the complete plate to the shape of the inside of the TLC. (See image B) You must bend it
 perfectly to match the inside shape or the double-sided tape will not hold the plate in place.
- Remove the cover on the double-sided tape.
- Before you stick the plate on firmly, make sure it is lined up perfectly so you see all the license plate numbers/ letters/ tags.
- Make sure you press firmly. If possible, use super glue, hot glue, or silicone to secure the plate. Be sure
 that when you install this TLC, the plate feels solid. One the TLC is installed on the drive hub, it will
 give some pressure to the backside of the license plate.

Installing the TLC:

- 1) First, you must support the bike so you can remove the shock on the shaft drive side.
- 2) Next, remove the shock.
- 3) Slide the SDC into place, with the shock mount going through the 1" hole in the SDC.
- 4) Install the supplied rubber washer so it sits between the SDC and the shock.
- 5) Lastly, re-install the shock
- 6) Check fit and firmness after your first ride of showing off your *Nice bike™*.







