

Contact Tech Support if you have any issues or questions

Techsupport@LowandMean.com or 928-680-6660

© 2006-2014 Low and Mean L.L.C.™, All rights reserved.



LED Flasher Light Bar Installation Instructions

LM-LF-2000, 2005, 2010, 2015



Scan the QR code to the left to be directed to the **How To Video** by Low and Mean

Let us know how your installation went. Send an email to techsupport@lowandmean.com



LM-LF-2000 this pn# comes with silver end caps. Black end caps have pn# LM-LF-2005



LM-LF-2015

Parts Included:

7" LED Flasher Bar (1)

2 Bolts and 2 Nuts

OR

3.5" LED Flasher Bars (2)

4 Bolts and 4 Nuts

READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION

7" LED Flasher Light Bar

- 1 Includes 2 bolts and 2 nuts for mounting to your license plate frame.
- 2 You can mount to the top or the bottom of the license plate frame.
- 3 Wiring: (The Long LED Flasher Light Bar has 5 wires)

Black is the ground
Orange is the brake light
Red is the running light
Yellow is a turn signal
Green is a turn signal



Pair of 3.5" LED Flasher Light Bars

- 1 Includes 4 bolts and 4 nuts for mounting to your license plate frame.
- 2 Mount one 3.5" LED Bar to the top and one 3.5" LED Bar to the Bottom of your vertical position license plate.
- 3 Wiring (Each 3.5" LED Flasher Light Bar has 4 wires)

Black is ground
Orange is the brake light
Red is the running light
Yellow is a turn signal (on one 3.5" bar)
Green is a turn signal (on one 3.5" bar)



When wiring the 3.5" LED Bar, you will need to connect both black wires one from each bar to your wiring harness, along with both Orange and Red wires. You will connect the appropriate turn signal wire (either Yellow or Green) to the corresponding wire to your harness depending on whether you have the left or right turn signal on top.